



# Stone Paint ستون باينت



+971 56 215 6447

info@marmocolors.com

www.marmocolors.com



marmocolors



# MARMO Stone Paints

## Premium Acrylic-Based Stone Paint with a Semi-Rough Finish

MARMO Stone Paint is a high-quality, water-based coating made from crushed natural marble aggregates bonded with pure acrylic resin. Its natural color is derived from marble without the use of oxides, offering a semi-rough texture ideal for finishing applications.

### Key Features

- **High UV Resistance:** Ensures longevity and protection from sunlight.
- **Superior Resistance to Atmospheric Pollution:** Withstands harsh environmental conditions.
- **Exceptional Durability:** Provides long-lasting performance.
- **Natural Stone Effect:** Mimics the texture of natural stone.
- **Excellent Adhesion:** Bonds effectively to various surfaces.
- **Water-Resistant for Vertical Surfaces:** Provides limited water resistance.
- **Easy Application:** Simplifies installation with minimal effort.
- **Eco-Friendly:** Environmentally sustainable product.
- **Pollutant Resistant:** Resists environmental contaminants effectively.
- **Minimizes Cracks:** Reduces surface cracking, lowering maintenance costs.
- **Lower Maintenance and Recoating Costs:** Improves façades durability.

### Recommended Applications

Suitable for both interior and exterior use on:

- Precast Concrete
- Cement-Plastered Walls
- GRC (Glass Reinforced Concrete) Elements
- LAS GRA Elements
- EIFS (Exterior Insulation and Finish Systems)
- Cement Boards
- Gypsum Boards

## Application Instructions

### Surface Preparation

- The coating's performance depends on proper surface preparation:
- Allow new concrete to cure for at least 28 days before coating.
- Ensure the substrate is strong enough to support the paint.
- Fill and rectify any substrate defects such as cracks, undulations, or pinholes.
- Clean the surface thoroughly, removing loose paint, dust, or debris.
- Treat fungus or algae with a fungicidal wash; leave for 24 hours, then rinse and clean thoroughly.
- Ensure the surface is dry before application.

### Mixing

MARMO Paint is a single-component, water-based product.

- Mix thoroughly before use.
- If required, dilute with a small amount of clean potable water.
- Use a low-speed mixer to ensure proper blending.

### Application Guidelines

- Temperature Range: Apply at temperatures between 5°C to 40°C.
- Method: Use only a Hopper Gun.
- Air Pressure: Maintain between 90 and 120 bars.
- Spray Angle: Ensure a 90° angle during application.
- Complete application from corner to corner or other natural breaks in a single session.

## Technical Specifications

Volume Solids:	82%
Appearance:	Paste
Density:	1.8 Kilogram/Litter
Flexibility:	High (Tested to ASTM D522)
Application Temperature:	+5°C UP +40°C
In-Service Temperature:	-20°C UP +80°C
Water Resistance:	Excellent
Colors:	Natural Marble Shades Only
Consumption:	1.8 Kilogram/m <sup>2</sup> /mm thickness
Finish:	Matte / Semi-Rough
Coverage:	3 to 5 Kilogram/m <sup>2</sup>
Drying Time:	18 hours at 35°C
Touch Dry:	3 hours
Packaging:	Available in 23 kilogram Buckets
Shelf Life:	3 months when stored properly



## Storage and Handling

- Store below 35°C in original, unopened containers.
- Ensure proper ventilation during application and drying.
- Dispose of waste and packaging responsibly, adhering to local regulations.
- Do not allow the product to enter waterways or soil.
- Keep out of reach of children.

## Health and Safety

- Use appropriate personal protective equipment (PPE) during application.
- Avoid inhaling vapors or spray; use air-supplied breathing equipment if spraying indoors.
- In case of eye contact, rinse immediately with water and seek medical advice.
- Wash skin with soap and water if splashed.
- Material Safety Data Sheets (MSDS) are available upon request.



**Moon White WZO**  
7412



**Moon White**  
7413



**Jasmine WZO**  
7451



**Jasmine**  
7452





**Bahama Beige**  
8102



**Desert Beige**  
8121



**Sunset**  
4677



**Twilight**  
4785





**Gulf Mist WZO**  
2947



**Gulf Mist**  
2948



**Mirage**  
2931





**Manhattan Grey**

1101



**Rock Gray**

1125

**Manufactured by**  
Light Art Stone Building Material Manufacturing



**Exclusive Agent**  
Twin Touch Plaster and Cladding Works L.L.C.  
Maleha Road, SHJ, UAE

+971 56 215 6447

info@twintouch.ae

www.twintouch.ae



Made In United Arab Emirates  
صنع في الإمارات العربية المتحدة